

		S	M	L	XL
A	head tube angle	69.5 °	69.5 °	69.5 °	69.5 °
B	head tube length	95.0 mm	100.0 mm	115.0 mm	125.0 mm
C	top tube horizontal	575.0 mm	600.0 mm	625.0 mm	650.0 mm
D	standover height	743.0 mm	774.0 mm	800.0 mm	835.1 mm
E	BB offset	-58.0 mm	-58.0 mm	-58.0 mm	-58.0 mm
F	BB height	312.0 mm	312.0 mm	312.0 mm	312.0 mm
G	wheel base	1,076.4 mm	1,101.8 mm	1,127.9 mm	1,153.7 mm
H	BB center to toptube center	325.0 mm	375.0 mm	415.0 mm	465.0 mm
I	BB center to top of seattube	390.0 mm	440.0 mm	480.0 mm	530.0 mm
J	seat angle	73.6 °	73.6 °	73.6 °	73.6 °
K	chainstay	425.0 mm	425.0 mm	425.0 mm	425.0 mm
L	reach	398.7 mm	422.3 mm	443.2 mm	465.5 mm
M	stack	599.0 mm	603.6 mm	617.7 mm	627.1 mm
N	stem length	60.0 mm	70.0 mm	80.0 mm	90.0 mm
O	trail	83.9 mm	83.9 mm	83.9 mm	83.9 mm