

Models	Frame Size Number	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack
Top Fuel Low geometry**	15.5"	27.5"	39.4	69.5 °	10.0	69.9 °	55.8	33.0	2.5	42.6	4.7	8.0	106.4	75.7	39.2	56.1
	17.5"	29"	41.9	68.5 °	9.0	70.0 °	59.3	33.0	3.9	43.3	5.1	8.0	111.1	75.0	42.7	57.7
	18.5"	29"	44.5	68.5 °	9.0	70.0 °	60.9	33.0	3.9	43.3	5.1	8.0	112.7	74.1	44.3	57.7
	19.5"	29"	47.0	68.5 °	10.0	70.0 °	62.5	33.0	3.9	43.3	5.1	8.0	114.4	74.5	45.7	58.7
	21.5"	29"	52.1	68.5 °	12.0	70.0 °	64.6	33.0	3.9	43.3	5.1	8.0	116.3	75.1	46.4	60.6
Top Fuel High geometry**	15.5"	27.5"	39.4	70.5 °	10.0	70.9 °	55.8	34.1	1.4	42.4	4.7	7.9	106.3	76.6	40.1	55.4
	17.5"	29"	41.9	69.4 °	9.0	70.9 °	59.2	34.1	2.8	43.2	5.1	7.9	110.9	75.3	43.6	57.0
	18.5"	29"	44.5	69.4 °	9.0	70.9 °	60.9	34.1	2.8	43.2	5.1	7.9	112.5	77.7	45.2	57.0
	19.5"	29"	47.0	69.4 °	10.0	70.9 °	62.5	34.1	2.7	43.2	5.1	7.9	114.3	80.1	46.6	58.0
	21.5"	29"	52.1	69.4 °	12.0	70.9 °	64.6	34.1	2.7	43.2	5.1	7.9	116.5	82.5	48.1	60.5
Procaliber	15.5"	27.5"	39.4	73.0 °	10.0	69.3 °	55.8	30.2	4.8	42.5	4.4	8.3	105.3	72.7	38.2	58.3
	17.5"	29"	41.9	72.5 °	9.0	69.5 °	59.9	31.1	5.8	43.5	5.1	8.3	109.8	75.0	41.2	59.5
	18.5"	29"	44.5	72.0 °	9.0	69.5 °	61.7	31.1	5.8	43.5	5.1	8.3	111.3	76.4	42.7	59.5
	19.5"	29"	47.0	72.0 °	10.0	69.5 °	63.8	31.1	5.8	43.5	5.1	8.3	113.2	77.8	44.2	60.4
	21.5"	29"	52.1	72.0 °	12.0	69.5 °	65.9	31.1	5.8	43.5	5.1	8.3	115.4	81.6	45.7	62.3
Superfly Carbon	15.5"	27.5"	36.8	73.0 °	10.0	69.3 °	55.8	30.2	4.8	42.5	4.4	8.5	105.3	72.1	37.2	58.3
	17.5"	29"	41.9	72.5 °	10.0	69.3 °	60.2	31.1	5.8	43.5	5.1	8.5	110.3	76.7	41.2	60.0
	18.5"	29"	44.4	72.3 °	10.0	69.6 °	62.0	31.1	5.8	43.5	5.1	8.3	111.6	77.9	42.7	60.1
	19.5"	29"	47.0	72.0 °	10.0	69.6 °	63.9	31.1	5.8	43.5	5.1	8.3	113.1	79.2	44.3	60.1
	21.5"	29"	52.1	72.0 °	12.0	69.6 °	65.9	31.1	5.8	43.5	5.1	8.3	115.2	82.9	45.7	61.9
	23"	29"	55.9	72.0 °	12.0	69.6 °	67.3	31.1	5.8	43.5	5.1	8.3	116.6	84.7	47.1	61.9
Superfly AL	15.5"	27.5"	36.8	73.0 °	10.0	69.3 °	55.8	30.2	4.8	42.5	4.4	8.5	105.3	72.1	37.2	58.3
	17.5"	29"	41.9	72.5 °	10.0	69.3 °	60.2	31.1	5.8	43.5	5.1	8.5	110.3	76.5	41.2	60.0
	18.5"	29"	44.4	72.3 °	10.0	69.6 °	62.0	31.1	5.8	43.5	5.1	8.3	111.6	77.6	42.7	60.1
	19.5"	29"	47.0	72.0 °	10.0	69.6 °	63.9	31.1	5.8	43.5	5.1	8.3	113.1	79.5	44.3	60.1
	21.5"	29"	52.1	72.0 °	12.0	69.6 °	65.9	31.1	5.8	43.5	5.1	8.3	115.2	82.3	45.7	61.9
	23"	29"	55.9	72.0 °	12.0	69.6 °	67.3	31.1	5.8	43.5	5.1	8.3	116.6	84.4	47.1	61.9
Superfly SS	15.5"	29"	36.8	73.0 °	10.0	69.3 °	57.0	31.1	5.8	43.5	5.1	8.5	107.7	74.7	38.6	60.0
	17.5"	29"	41.9	72.5 °	10.0	69.3 °	60.2	31.1	5.8	43.5	5.1	8.5	110.3	76.5	41.2	60.0
	18.5"	29"	44.4	72.3 °	10.0	69.6 °	62.0	31.1	5.8	43.5	5.1	8.3	111.6	77.6	42.7	60.1
	19.5"	29"	47.0	72.0 °	10.0	69.6 °	63.9	31.1	5.8	43.5	5.1	8.3	113.1	79.5	44.3	60.1
	21.5"	29"	52.1	72.0 °	12.0	69.6 °	65.9	31.1	5.8	43.5	5.1	8.3	115.2	82.3	45.7	61.9
	23"	29"	55.9	72.0 °	12.0	69.6 °	67.3	31.1	5.8	43.5	5.1	8.3	116.6	84.4	47.1	61.9
Superfly Carbon WSD	13.5"	27.5"	34.3	73.0 °	10.0	69.0 °	54.1	30.2	4.8	42.5	4.4	8.7	103.7	71.0	37.0	56.3
	15.5"	27.5"	36.8	73.0 °	10.0	69.3 °	55.8	30.2	4.8	42.5	4.4	8.5	105.3	72.1	37.2	58.3
	17.5"	29"	41.9	72.5 °	10.0	69.3 °	60.2	31.1	5.8	43.5	5.1	8.5	110.3	76.7	41.2	60.0
	18.5"	29"	44.4	72.3 °	10.0	69.6 °	62.0	31.1	5.8	43.5	5.1	8.3	111.6	77.9	42.7	60.1
Superfly AL WSD	13.5"	27.5"	34.3	73.0 °	10.0	69.0 °	54.1	30.2	4.8	42.5	4.4	8.7	103.7	71.0	37.0	56.3
	15.5"	27.5"	36.8	73.0 °	10.0	69.3 °	55.8	30.2	4.8	42.5	4.4	8.5	105.3	72.1	37.2	58.3
	17.5"	29"	41.9	72.5 °	10.0	69.3 °	60.2	31.1	5.8	43.5	5.1	8.5	110.3	76.5	41.2	60.0
	18.5"	29"	44.4	72.3 °	10.0	69.6 °	62.0	31.1	5.8	43.5	5.1	8.3	111.6	77.6	42.7	60.1
X-Caliber	13.5"	27.5"	34.3	73.0 °	10.0	69.0 °	52.5	30.6	4.8	43.8	4.4	8.9	103.3	66.0	35.2	56.5
	15.5"	27.5"	39.4	73.0 °	10.0	69.3 °	56.0	30.6	4.8	43.8	4.4	8.7	106.6	74.5	38.1	58.5
	17.5"	29"	41.9	72.5 °	10.0	69.3 °	60.2	31.6	5.3	44.5	5.1	8.5	111.6	76.5	41.3	60.0
	18.5"	29"	44.4	72.3 °	10.0	69.6 °	62.0	31.6	5.3	44.5	5.1	8.3	112.8	77.7	42.8	60.1
	19.5"	29"	47.0	72.0 °	10.0	69.6 °	63.9	31.6	5.3	44.5	5.1	8.3	114.4	78.9	44.4	60.1
	21.5"	29"	52.1	72.0 °	12.0	69.6 °	65.9	31.6	5.3	44.5	5.1	8.3	116.5	82.5	45.8	62.0
Cali	13.5"	27.5"	34.3	73.0 °	10.0	69.0 °	52.5	30.6	4.8	43.8	4.4	8.9	103.3	66.0	35.2	56.5
	15.5"	27.5"	39.4	73.0 °	10.0	69.3 °	56.0	30.6	4.8	43.8	4.4	8.7	106.6	74.5	38.1	58.5
	17"	29"	40.6	73.0 °	10.0	69.0 °	59.0	31.2		44.5	5.1	8.5	111.3	66.9	40.7	59.8
	18.5"	29"	44.5	73.0 °	10.0	69.0 °	61.2	31.2		44.5	5.1	8.5	113.5	68.5	42.9	59.8

Models	Frame Size Number	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack
Fuel EX 5 & 7 29	15.5"	29"	39.4	73.6°	10.5	69.5°	56.7	33.8	3.2	45.2	5.1	8.4	110.8	77.9	39.0	60.1
	17.5"	29"	42.0	73.6°	10.5	69.5°	59.8	33.8	3.2	45.2	5.1	8.4	113.9	76.5	42.1	60.1
	18.5"	29"	44.5	73.6°	11.5	69.5°	61.2	33.8	3.2	45.2	5.1	8.4	115.4	77.3	43.2	61.1
	19.5"	29"	47.0	73.6°	11.5	69.5°	62.7	33.8	3.2	45.2	5.1	8.4	116.9	76.8	44.7	61.1
	21.5"	29"	50.8	73.6°	13.0	69.5°	65.0	33.8	3.2	45.2	5.1	8.4	119.3	77.0	46.6	62.5
	23"	29"	55.9	73.6°	14.5	69.5°	66.3	33.8	3.2	45.2	5.1	8.4	120.7	78.8	47.5	63.9
Fuel EX 29 Low geometry**	15.5"	29"	39.4	67.0°	10.5	68.8°	57.2	33.4	3.6	43.6	5.1	8.9	110.5	78.0	39.5	60.2
	17.5"	29"	42.0	67.0°	10.5	68.8°	60.3	33.4	3.6	43.6	5.1	8.9	113.6	76.6	42.6	60.2
	18.5"	29"	44.5	67.0°	11.5	68.8°	61.7	33.4	3.6	43.6	5.1	8.9	115.1	78.0	43.7	61.1
	19.5"	29"	47.0	67.0°	11.5	68.8°	63.2	33.4	3.6	43.6	5.1	8.9	116.6	77.3	45.2	61.1
	21.5"	29"	50.8	67.0°	13.0	68.8°	65.5	33.4	3.6	43.6	5.1	8.9	119.0	78.3	47.1	62.5
	23"	29"	55.9	67.0°	14.5	68.8°	66.8	33.4	3.6	43.6	5.1	8.9	120.5	78.4	48.0	63.9
Fuel EX 29 High geometry**	15.5"	29"	39.4	67.7°	10.5	69.4°	57.0	34.2	2.3	43.4	5.1	8.9	110.4	78.7	40.2	59.7
	17.5"	29"	42.0	67.7°	10.5	69.4°	60.1	34.2	2.3	43.4	5.1	8.9	113.5	77.3	43.3	59.7
	18.5"	29"	44.5	67.7°	11.5	69.4°	61.5	34.2	2.3	43.4	5.1	8.9	115.0	78.7	44.4	60.6
	19.5"	29"	47.0	67.7°	11.5	69.4°	63.0	34.2	2.3	43.4	5.1	8.9	116.5	78.0	45.9	60.6
	21.5"	29"	50.8	67.7°	13.0	69.4°	65.3	34.2	2.3	43.4	5.1	8.9	118.9	79.0	47.8	62.0
	23"	29"	55.9	67.7°	14.5	69.4°	66.6	34.2	2.3	43.4	5.1	8.9	120.4	79.2	48.7	63.4
Fuel EX 27.5	15.5"	27.5"	36.8	73.0°	9.5	68.0°	55.5	33.3	1.7	43.3	4.4	8.4	110.1	74.0	37.4	56.0
	17.5"	27.5"	41.9	73.0°	10.0	68.0°	58.8	33.3	1.7	43.3	4.4	8.4	113.7	73.0	41.5	65.5
	18.5"	27.5"	44.5	73.0°	11.0	68.0°	60.8	33.3	1.7	43.3	4.4	8.4	115.5	73.0	43.2	57.4
	19.5"	27.5"	47.0	73.0°	12.0	68.0°	62.7	33.3	1.7	43.3	4.4	8.4	117.0	74.0	44.9	58.3
	21.5"	27.5"	52.1	73.0°	14.0	68.0°	65.3	33.3	1.7	43.3	4.4	8.4	119.4	74.2	46.9	60.2
Lush Carbon	14"	27.5"	35.5	74.0°	9.5	68.0°	53.0	33.5	1.5	43.3	4.4	9.4	107.0	69.1	37.0	55.9
	15.5"	27.5"	39.4	74.0°	9.5	68.0°	55.0	33.5	1.5	43.3	4.4	9.4	109.0	68.8	39.0	55.9
	17"	27.5"	40.6	74.0°	10.5	68.0°	58.0	33.5	1.5	43.3	4.4	9.4	112.1	68.7	41.7	56.8
	18.5"	27.5"	44.5	74.0°	12.0	68.0°	60.5	33.5	1.5	43.3	4.4	9.4	114.7	69.0	43.8	58.2
Lush AL	14"	27.5"	35.5	74.0°	9.5	68.0°	53.0	33.5	1.5	43.3	4.4	9.4	107.0	69.1	37.0	55.9
	15.5"	27.5"	39.4	74.0°	9.5	68.0°	55.0	33.5	1.5	43.3	4.4	9.4	109.0	68.2	39.0	55.9
	17"	27.5"	40.6	74.0°	10.5	68.0°	58.0	33.5	1.5	43.3	4.4	9.4	112.1	68.7	41.7	56.8
	18.5"	27.5"	44.5	74.0°	12.0	68.0°	60.5	33.5	1.5	43.3	4.4	9.4	114.7	68.8	43.8	58.2
Stache 9 Stache 7	15.5"	29"	39.4	68.9°	9.0	68.4°	56.3	32.9	6.1	42	5.1	10.0	107.1	79.8	37.9	62.1
	17.5"	29"	41.9	68.9°	9.0	68.4°	59.1	32.9	6.1	42	5.1	10.0	109.9	80.9	40.7	62.1
	18.5"	29"	44.5	68.9°	10.0	68.4°	60.9	32.9	6.1	42	5.1	10.0	111.7	82.0	42.1	63.0
	19.5"	29"	47.0	68.9°	10.0	68.4°	62.4	32.9	6.1	42	5.1	10.0	113.2	80.8	43.6	63.0
	21.5"	29"	52.1	68.9°	11.0	68.4°	64.6	32.9	6.1	42	5.1	10.0	115.5	80.8	45.6	64.0
Stache 5	15.5"	29"	39.4	70.9°	9.0	70.4°	55.5	31.4	7.6	42	5.1	10.0	105.7	77.8	40.1	60.7
	17.5"	29"	41.9	70.9°	9.0	70.4°	58.3	31.4	7.6	42	5.1	10.0	108.5	79.1	42.9	60.6
	18.5"	29"	44.5	70.9°	10.0	70.4°	60.1	31.4	7.6	42	5.1	10.0	110.3	80.3	44.3	61.5
	19.5"	29"	47.0	70.9°	10.0	70.4°	61.6	31.4	7.6	42	5.1	10.0	111.8	79.2	45.8	61.5
	21.5"	29"	52.1	70.9°	11.0	70.4°	63.8	31.4	7.6	42	5.1	10.0	114.0	79.2	47.7	62.4
Farley	15.5"	26"	36.8	73.0°	10.0	70.0°	56.6	31.3	5.5	44.0	4.6	8.5	106.3	77.0	38.4	59.5
	17.5"	26"	41.9	73.0°	10.0	70.0°	59.3	31.3	5.5	44.0	4.6	8.5	109.0	78.2	41.1	59.5
	19.5"	26"	47.0	73.0°	12.0	70.0°	63.0	31.3	5.5	44.0	4.6	8.5	112.8	81.7	44.2	61.3
	21.5"	26"	52.1	73.0°	12.0	70.0°	64.3	31.3	5.5	44.0	4.6	8.5	114.1	83.2	45.5	61.3
Remedy Carbon 27.5 Low geometry**	15.5"	27.5"	39.4	67.5°	10.0	67.5°	54.9	33.8	1.5	43.5	4.3	10.0	109.8	77.2	36.6	59.3
	17.5"	27.5"	41.9	67.5°	10.0	67.5°	58.2	33.8	1.5	43.5	4.3	10.0	113.1	75.8	39.4	69.4
	18.5"	27.5"	44.5	67.5°	10.5	67.5°	60.1	33.8	1.5	43.5	4.3	10.0	115.1	74.4	41.7	69.9
	19.5"	27.5"	47.0	67.5°	11.0	67.5°	61.8	33.8	1.5	43.5	4.3	10.0	116.7	74.2	43.2	60.4
	21.5"	27.5"	50.8	67.5°	12.5	67.5°	64.6	33.8	1.5	43.5	4.3	10.0	119.6	73.9	45.5	61.8
Remedy Carbon 27.5 High geometry**	15.5"	27.5"	39.4	68.2°	10.0	68.2°	54.6	34.6	.7	43.3	4.3	9.5	109.7	77.9	37.3	58.9
	17.5"	27.5"	41.9	68.2°	10.0	68.2°	57.9	34.6	.7	43.3	4.3	9.5	113.0	76.5	40.6	58.9
	18.5"	27.5"	44.5	68.1°	10.5	68.1°	59.8	34.6	.7	43.3	4.3	9.5	114.9	75.1	42.4	59.4
	19.5"	27.5"	47.0	68.1°	11.0	68.1°	61.5	34.6	.7	43.3	4.3	9.5	116.6	74.9	43.9	59.9
	21.5"	27.5"	50.8	68.1°	12.5	68.1°	64.3	34.6	.7	43.3	4.3	9.5	119.3	74.6	46.1	61.3

Models	Frame Size Number	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack
Remedy AL 27.5 Low geometry**	15.5"	27.5"	39.4	67.5 °	10.0	67.5 °	54.9	33.8	1.5	43.5	4.3	10.0	109.8	77.6	36.6	59.3
	17.5"	27.5"	41.9	67.5 °	10.0	67.5 °	58.2	33.8	1.5	43.5	4.3	10.0	113.1	75.8	39.4	69.4
	18.5"	27.5"	44.5	67.5 °	10.5	67.5 °	60.1	33.8	1.5	43.5	4.3	10.0	115.1	74.4	41.7	69.9
	19.5"	27.5"	47.0	67.5 °	11.0	67.5 °	61.8	33.8	1.5	43.5	4.3	10.0	116.7	74.0	43.2	60.4
	21.5"	27.5"	50.8	67.5 °	12.5	67.5 °	64.6	33.8	1.5	43.5	4.3	10.0	119.6	74.5	45.5	61.8
Remedy AL 27.5 High geometry**	15.5"	27.5"	39.4	68.2 °	10.0	68.2 °	54.6	34.6	.7	43.3	4.3	9.5	109.7	78.2	37.3	58.9
	17.5"	27.5"	41.9	68.2 °	10.0	68.2 °	57.9	34.6	.7	43.3	4.3	9.5	113.0	76.5	40.6	58.9
	18.5"	27.5"	44.5	68.1 °	10.5	68.1 °	59.8	34.6	.7	43.3	4.3	9.5	114.9	75.1	42.4	59.4
	19.5"	27.5"	47.0	68.1 °	11.0	68.1 °	61.5	34.6	.7	43.3	4.3	9.5	116.6	74.7	43.9	59.9
	21.5"	27.5"	50.8	68.1 °	12.5	68.1 °	64.3	34.6	.7	43.3	4.3	9.5	119.3	75.3	46.1	61.3
Remedy Carbon 29 Low geometry**	15.5"	29"	39.4	68.0 °	10.0	67.5 °	54.6	35.0	2.0	44.5	5.1	9.8	112.8	77.1	38.6	60.5
	17.5"	29"	41.9	68.0 °	10.0	67.5 °	57.6	35.0	2.0	44.5	5.1	9.8	115.8	76.7	41.6	60.5
	18.5"	29"	44.5	68.0 °	10.5	67.5 °	59.4	35.0	2.0	44.5	5.1	9.8	117.5	74.5	43.2	60.9
	19.5"	29"	47.0	68.0 °	11.0	67.5 °	60.9	35.0	2.0	44.5	5.1	9.8	119.0	75.1	44.7	60.9
	21.5"	29"	52.1	68.0 °	12.5	67.5 °	63.1	35.0	2.0	44.5	5.1	9.8	121.2	76.6	46.5	61.9
Remedy Carbon 29 High geometry**	15.5"	29"	39.4	69.0 °	10.0	68.2 °	54.4	35.9	2.0	44.3	5.1	9.3	112.6	77.9	39.3	60.0
	17.5"	29"	41.9	69.0 °	10.0	68.2 °	57.3	35.9	2.0	44.3	5.1	9.3	115.6	77.5	42.3	60.0
	18.5"	29"	44.5	69.0 °	10.5	68.2 °	59.1	35.9	2.0	44.3	5.1	9.3	117.4	75.3	43.9	60.4
	19.5"	29"	47.0	69.0 °	11.0	68.2 °	60.6	35.9	2.0	44.3	5.1	9.3	118.9	75.9	45.4	60.4
	21.5"	29"	52.1	69.0 °	12.5	68.2 °	62.8	35.9	2.0	44.3	5.1	9.3	121.1	77.5	47.2	61.3
Remedy AL 29 Low geometry**	15.5"	29"	39.4	68.0 °	10.0	67.5 °	54.6	35.0	2.0	44.5	5.1	9.8	112.8	77.9	38.5	60.6
	17.5"	29"	41.9	68.0 °	10.0	67.5 °	57.6	35.0	2.0	44.5	5.1	9.8	115.8	76.5	41.5	60.6
	19"	29"	45.7	68.0 °	10.5	67.5 °	59.7	35.0	2.0	44.5	5.1	9.8	117.9	76.8	43.4	61.1
	21"	29"	50.8	68.0 °	11.0	67.5 °	61.8	35.0	2.0	44.5	5.1	9.8	120.0	78.1	45.1	62.0
	23"	29"	55.9	68.0 °	12.5	67.5 °	63.9	35.0	2.0	44.5	5.1	9.8	122.1	81.8	46.9	62.9
Remedy AL 29 High geometry**	15.5"	29"	39.4	69.0 °	10.0	68.2 °	54.4	35.9	2.0	44.3	5.1	9.3	112.7	76.9	39.3	60.6
	17.5"	29"	41.9	69.0 °	10.0	68.2 °	57.4	35.9	2.0	44.3	5.1	9.3	115.7	75.5	42.3	60.6
	19"	29"	45.7	69.0 °	10.5	68.2 °	59.4	35.9	2.0	44.3	5.1	9.3	117.7	75.8	44.1	61.1
	21"	29"	50.8	69.0 °	11.0	68.2 °	61.5	35.9	2.0	44.3	5.1	9.3	119.8	77.1	45.9	62.0
	23"	29"	55.9	69.0 °	12.5	68.2 °	63.6	35.9	2.0	44.3	5.1	9.3	121.9	80.8	47.6	62.9
Slash Low geometry**	15.5"	27.5"	39.4	66.5 °	10.0	65.0 °	55.7	35.0	.6	43.5	4.4	11.7	114.9	79.5	39.7	58.1
	17.5"	27.5"	41.9	66.5 °	10.0	65.0 °	58.7	35.0	.6	43.5	4.4	11.7	117.9	77.7	42.7	58.1
	18.5"	27.5"	44.5	66.5 °	10.0	65.0 °	60.0	35.0	.6	43.5	4.4	11.7	119.2	76.2	44.0	58.1
	19.5"	27.5"	47.0	66.5 °	11.0	65.0 °	61.4	35.0	.6	43.5	4.4	11.7	120.5	75.6	45.0	59.0
	21.5"	27.5"	52.1	66.5 °	12.0	65.0 °	64.2	35.0	.6	43.5	4.4	11.7	123.4	74.5	47.4	59.9
Slash High geometry**	15.5"	27.5"	39.4	67.2 °	10.0	65.7 °	55.5	35.8	-.2	43.3	4.4	11.7	114.7	80.2	40.4	57.6
	17.5"	27.5"	41.9	67.1 °	10.0	65.6 °	58.5	35.8	-.2	43.3	4.4	11.7	117.7	78.4	43.4	57.6
	18.5"	27.5"	44.5	67.1 °	10.0	65.6 °	59.8	35.8	-.2	43.3	4.4	11.7	119.0	76.9	44.7	57.6
	19.5"	27.5"	47.0	67.1 °	11.0	65.6 °	61.1	35.9	-.3	43.3	4.4	11.7	120.4	76.4	45.6	58.5
	21.5"	27.5"	52.1	67.1 °	12.0	65.6 °	64.5	35.9	-.3	43.3	4.4	11.7	123.2	75.3	48.0	59.4
Session DH Low geometry**	S	27.5"	39.0	57.0 °	11.5	63.6 °	47.7	35.6	1.0	44.5	5.2	11.8	118.3	80.4	38.2	60.7
	M	27.5"	39.0	57.0 °	11.5	63.6 °	51.5	35.6	1.0	44.5	5.2	11.8	120.3	79.0	40.2	60.7
	L	27.5"	39.0	57.0 °	11.5	63.6 °	53.9	35.6	1.0	44.5	5.2	11.8	122.7	78.4	42.6	60.7
	XL	27.5"	39.0	57.0 °	11.5	63.6 °	58.4	35.6	1.0	44.5	5.2	11.8	125.1	76.7	45.0	60.7
Session DH High geometry**	S	27.5"	39.0	57.6 °	11.5	64.2 °	57.0	36.4	1.4	44.3	5.2	11.4	118.5	81.0	38.9	60.3
	M	27.5"	39.0	57.6 °	11.5	64.2 °	59.0	36.4	1.4	44.3	5.2	11.4	120.5	79.3	40.8	60.3
	L	27.5"	39.0	57.6 °	11.5	64.2 °	61.4	36.4	1.4	44.3	5.2	11.4	122.9	79.0	43.2	60.3
	XL	27.5"	39.0	57.6 °	11.5	64.2 °	63.8	36.4	1.4	44.3	5.2	11.4	125.3	77.5	45.6	60.3
Session Park Low geometry**	M	26"	44.0	57.0 °	12.5	63.6 °	58.6	35.6	1.3	42.0	4.5	12.0	116.3	74.7	39.2	59.3
	L	26"	44.0	57.0 °	12.5	63.6 °	61.0	35.6	1.3	42.0	4.5	12.0	118.8	74.7	41.7	59.3
Session Park High geometry**	M	26"	44.0	57.6 °	12.5	64.2 °	58.2	36.4	2.1	41.8	4.5	11.9	116.0	75.4	39.8	58.8
	L	26"	44.0	57.6 °	12.5	64.2 °	60.7	36.4	2.1	41.8	4.5	12.0	118.0	75.4	42.3	58.9
Ticket Low geometry**	Long	26"	33.1	75.0 °	12.3	68.5 °	56.5	33.0	0.3	40.0	4.0	8.8	108.5	37.5	42.6	55.3
Ticket High geometry**	Long	26"	33.1	75.8 °	12.3	69.3 °	56.3	33.9	0.6	39.8	4.0	8.8	108.3	38.3	43.3	54.7

Models	Frame Size Number	Wheel size	A - Seat tube	B - Seat tube angle	C - Head tube length	D - Head angle	E - Effective top tube	F - Bottom bracket height	G - Bottom bracket drop	H - Chainstay length	I - Offset	J - Trail	K - Wheelbase	L - Standover	M - Frame reach	N - Frame stack
Ticket DJ	Long	26"	33.0	71.0 °	12.0	70.0 °	57.0	32.0	1.2	39.8	4.0	7.7	105.0	69.1	41.4	54.3
Marlin	13.5"	27.5"	34.3	73.0 °	10.0	69.0 °	52.5	30.6	4.8	43.8	4.4	8.9	103.3	66.0	35.2	56.5
	15.5"	27.5"	39.4	73.0 °	10.0	69.3 °	56.0	30.6	4.8	43.8	4.4	8.7	106.6	74.5	38.1	58.5
	17.5"	29"	41.9	72.5 °	10.0	69.3 °	60.2	31.6	5.3	44.5	5.1	8.5	111.6	76.5	41.3	60.0
	18.5"	29"	44.4	72.3 °	10.0	69.6 °	62.0	31.6	5.3	44.5	5.1	8.3	112.8	77.7	42.8	60.1
	19.5"	29"	47.0	72.0 °	10.0	69.6 °	63.9	31.6	5.3	44.5	5.1	8.3	114.4	78.9	44.4	60.1
	21.5"	29"	52.1	72.0 °	12.0	69.6 °	65.9	31.6	5.3	44.5	5.1	8.3	116.5	82.5	45.8	62.0
	23"	29"	55.9	72.0 °	12.0	69.6 °	67.3	31.6	5.3	44.5	5.1	8.3	117.9	84.8	47.2	62.0
Skye SL Disc	13.5"	27.5"	34.3	73.0 °	10.0	69.0 °	52.5	30.6	4.8	43.8	4.4	8.9	103.3	66.0	35.2	56.5
Skye S Disc	15.5"	27.5"	39.4	73.0 °	10.0	69.3 °	56.0	30.6	4.8	43.8	4.4	8.7	106.6	68.0	38.1	58.5
	17"	29"	40.6	73.0 °	10.0	69.0 °	59.0	31.2		44.5	5.1	8.5	111.3	66.9	40.7	59.8
	18.5"	29"	44.5	73.0 °	10.0	69.0 °	61.2	31.2		44.5	5.1	8.5	113.5	68.5	42.9	59.8
Skye 26	13"	26"	33.0	74.0 °	11.0	70.5 °	52.4	28.7		43.0	4.0	7.6	101.9	65.5		
	16"	26"	40.6	73.5 °	11.0	70.5 °	54.6	29.1		43.0	4.0	7.6	103.6	63.1		
	19.5"	26"	49.5	73.0 °	17.0	70.5 °	57.5	29.3		43.0	4.0	7.6	106.4	62.5		
3 Series	13"	26"	33.0	74.0 °	11.0	70.5 °	52.4	28.7		43.0	4.0	7.6	101.9	70.5		
	16"	26"	40.6	73.5 °	11.0	70.5 °	55.0	29.1		43.0	4.0	7.6	104.0	73.8		
	18"	26"	45.7	73.5 °	13.0	70.5 °	56.5	29.3		43.0	4.0	7.6	105.7	77.2		
	19.5"	26"	49.5	73.0 °	15.0	70.5 °	58.0	29.3		43.0	4.0	7.6	106.8	79.9		
	21"	26"	53.3	73.0 °	17.0	70.5 °	59.0	29.3		43.0	4.0	7.6	107.9	82.7		
	22.5"	26"	57.2	72.5 °	19.0	70.5 °	60.0	29.5		43.0	4.0	7.6	108.4	85.7		
Police	15.5"	29"	39.4	73.0 °	10.3	69.3 °	57.0	31.2	5.3	44.5	5.1	8.3	109.0	75.4	38.6	60.2
	17.5"	29"	44.5	72.5 °	10.3	69.3 °	60.2	31.2	5.3	44.5	5.1	8.3	111.6	77.5	41.2	60.2
	19"	29"	48.3	72.0 °	10.3	69.6 °	62.2	31.2	5.3	44.5	5.1	8.1	112.7	79.5	42.6	60.3
	21"	29"	53.3	72.0 °	11.8	69.6 °	64.3	31.2	5.3	44.5	5.1	8.1	114.8	82.8	44.2	61.7
	23"	29"	58.4	72.0 °	11.8	69.6 °	66.3	31.2	5.3	44.5	5.1	8.1	116.9	85.9	46.2	61.7
Powerfly+ FS	15.5"	29"	36.8	71.0 °	13.0	68.0 °	55.5	33.3	1.7	47.0	4.4	9.4	110.1	73.0	38.9	59.5
	17.5"	29"	41.9	71.0 °	13.2	68.0 °	58.0	33.3	1.7	47.0	4.4	9.4	112.6	73.0	42.2	59.5
	18.5"	29"	44.5	71.0 °	14.0	68.0 °	60.5	33.3	1.7	47.0	4.4	9.4	115.1	73.0	39.8	60.2
	19.5"	29"	47.0	71.0 °	14.0	68.0 °	62.7	33.3	1.7	47.0	4.4	9.4	117.3	73.0	42.0	60.2
	21.5"	29"	52.1	71.0 °	16.0	68.0 °	65.3	33.3	1.7	47.0	4.4	9.4	120.0	73.0	43.9	62.1
Powerfly+	15.5"	29"	40.0	73.0 °	14.0	69.0 °	56.1	33.2	5.3	48.5	5.1		112.0	78.8	36.5	63.8
	17.5"	29"	42.5	72.5 °	14.0	69.0 °	58.3	33.2	5.3	48.5	5.1		113.7	79.0	38.2	63.8
	19"	29"	47.0	72.5 °	16.0	69.0 °	60.7	33.2	5.3	48.5	5.1		116.2	81.1	40.0	65.6
	21"	29"	51.5	72.5 °	16.0	69.0 °	63.2	33.2	5.3	48.5	5.1		118.7	84.3	42.5	65.6
Powerfly+ WSD	15.5"	29"	40.0	73.0 °	14.0	69.0 °	55.5	32.0	4.8	46.5	4.4		109.5	72.5	36.5	62.1
	17.5"	29"	42.5	72.5 °	14.0	69.0 °	57.8	32.0	4.8	46.5	4.4		111.2	72.0	38.2	62.1