

Actual frame size	15.5 in	17.5 in	18.5 in	19.5 in	21.5 in
Geometry position	Low	Low	Low	Low	Low
Wheel size	27.5"	27.5"	27.5"	27.5"	27.5"
A Seat tube	36.8	41.9	44.5	47.0	52.1
B Seat tube angle	71.5°	71.5°	71.5°	71.5°	71.5°
Effective seat tube angle	73.5°	73.5°	73.5°	73.5°	73.5°
C Head tube length	10.0	10.0	10.5	11.0	12.5
D Head angle	66.9°	66.9°	66.9°	66.9°	66.9°
E Effective top tube	57.0	60.0	62.0	63.4	66.2
F Bottom bracket height	33.2	33.2	33.2	33.2	33.2
G Bottom bracket drop	2.4	2.4	2.4	2.4	2.4
H Chainstay length	47.4	47.4	47.4	47.4	47.4
I Offset	5.1	5.1	5.1	5.1	5.1
J Trail	8.8	8.9	8.9	8.9	8.9
K Wheelbase	117.7	120.7	122.8	124.3	127.3
L Standover	76.0	74.0	73.5	73.0	74.0
M Frame reach	40.5	43.5	45.3	46.6	49.0
N Frame stack	59.4	59.3	59.8	60.2	61.6